#### MATERIAL SAFETY DATA SHEET

1 Flammability = Reactivity = NFPA RATING: Health = Reactivity = Flammability = HMIS RATING: Health =

ECTION I – IDENTITY AND MANUFACTURER'S INFORMATION

(0539E)

Manufacturer's Name:

HILLYARD INDUSTRIES

Product Name: CONTENDER FINISH (PARTS A & B)

Address:

302 North Fourth Street

Date Prepared: August 1, 1995

St. Joseph, MO 64501

Regulatory Affairs Department Prepared by:

Emergency Telephone No.: (800)-424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident

Other information calls: (816)233-1321(Ext. 303) involving chemicals.)

### SECTION II - INGREDIENTS/IDENTITY INFORMATION

Components (Specific Chemical Identity:	CAS#	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDE D	%
Common Name(s)	107-98-2	100 ppm	100 ppm	N/A	7-10
Propylene glycol monomethyl ether (1)	7732-18-5	none	none	N/A	
Water Aminated acrylic polymer-chloride and bromide salt	103051-70-3	none	none	N/A	_
Leveling agents	Unknown to	none	none	N/A	-
Dovoining agoing	Hillyard Ind.				
Reaction products of Epichlorohydrin and Bisphenol A Diepoxide Pyrol	25085-99-8	none	none	N/A N/A	
	Unknown to	none	none		<del></del>
	Hillyard Ind.				
Gamma-butyrolactone(2) Epichlorohydrin-Polyglycol Reaction Product	96-48-0	none	none	N/A	1-4
	26142-30-3	none	none	N/A	
TO BE A STATE OF THE TANKS NO DA DI					

(1) Regulated by OSHA, FL, IL, LA, MA, NJ, PA, RI

(2) Regulated by TX.

### CTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

Specific Gravity (H20 = 1): 25°C = 1.05 203°F **Boiling Point:** corr.

average 72.4 Percent Volatile by Volume (%): Vapor Pressure (mm Hg.): 17.2 slower than 1 Evaporation Rate (ethyl ether = 1):

0.6 Vapor Density (AIR = 1): white, opaque liquid Appearance and Odor: appreciable Solubility in Water:

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

UEL = N/Anot determined Flammable Limits: LEL = Flash point: None (T.C.C.)

Extinguishing Media: Carbon dioxide, dry chemical, fog or water spray

Special Fire Fighting Procedures: Self-contained breathing apparatus with full facepiece operated in pressure demand or other

Unusual Fire and Explosion Hazards: May form carbon dioxide and carbon monoxide.

#### SECTION V - PHYSICAL HAZARDS

Conditions to Avoid: N/A Stability: Stable Incompatibility (Materials to Avoid): Fire and excess heat; strong acids

Hazardous Decomposition Products or Byproducts: Carbon monoxide, carbon dioxide and products of combustion of

organic material.

Conditions to Avoid: N/A Will not occur Hazardous Polymerization:

#### SECTION VI - HEALTH HAZARD DATA

Skin? Yes Ingestion? No Routes of entry: Inhalation?

#### **HEALTH HAZARDS (1. Acute and 2. Chronic)**

1. Eye irritant. Prolonged exposure to skin may cause discomfort and dermatitis. Causes nose and throat irritation. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

2. Reports have associated repeated and prolonged occupational overexposure to solvent with permanent brain and nervous system damage. Epoxy resins are capable of causing sensitization of skin; sensitivity varies from person to person.

## SECTION VI - HEALTH HAZARD DATA cont.

Chemical listed as Carcinogen or Potential Carcinogen:

National Toxicology Program = No I.A.R.C. Monographs = This product has no carcinogens listed by IARC, NTP, NIOSH, or ACGIH as of this date, greater than or equal to 0.1%. No

Signs and Symptoms of Exposure: Product is not a primary eye or skin irritant per Federal Hazardous Substance Act, CFR 16, Chapter IIc, Paragraph 1500.41 and 1500.42. Overexposure to propylene glycol monomethyl ether may cause mild eye, nose and throat irritation; headache, nausea and Central Nervous System depression.

Medical Conditions Generally Aggravated by Exposure: None known to Hillyard.

Emergency and First Aid Procedures: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact immediately flush with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Call a physician

# SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: If spilled contain spilled material and remove with inert absorbent. Do not let spilled or leaking material enter watercourse.

Waste Disposal Method: Collect absorbent/spilled mixture into plastic containers. Dispose of contaminated absorbent, container and unused contents in accordance with federal, state and local regulations.

Precautions To Be Taken In Handling And Storing: Keep containers closed tightly when not in use. Store in cool, well ventilated areas away from heat and out of direct sunlight. Protect from freezing.

Other Precautions: Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not take internally. This product contains no reportable quantities of toxic chemicals subject to reporting requirements of Section 313 of SARA Title III Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR Part 372.

### SECTION VIII - CONTROL MEASURES:

Respiratory Protection (Specify Type): If sprayed, use respirator MESA/NIOSH approved for mist and organic vapor. None normally

Ventilation:

Local Exhaust = N/A Mechanical (General) = Adequate ventilation required Special = N/A Other = N/A **Protective Gloves:** 

Rubber or neoprene gloves Eye Protection: None normally needed Other Protective Clothing or Equipment: To prevent repeated or prolonged contact, wear impervious clothing and boots.

Work / Hygienic Practices: Wash hands before eating or using washroom.

# SECTION IX - TRANSPORTATION INFORMATION:

Applicable regulations: 49 CFR =  $\underline{no}$ ; IMCO =  $\underline{no}$ ; IATA =  $\underline{no}$ .

Proper shipping name: Vanish

UN No.: not applicable; Limited Qty.: not applicable; Hazard Class: not applicable.

Labels required: not required DOT Exception: not applicable

EPA Hazardous waste number / code: not listed

Hazardous waste characteristics:

Ignitability = not applicable; Corrosivity = not applicable; Reactivity = not applicable.

### DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.

The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate.

THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.

