

SECTION 1

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

POWER PUNCH DISTRIBUTORS LLC
5959 STATE HWY 303 NE, SUITE 103
BREMERTON, WA. 98311

PHONE NUMBERS

Business Hours: (360) 479-0673
 24 Hours: Chemtrec: (800) 424-9300
 General MSDS: (360) 479-0673

Product Name: **Power Punch Oil Supplements**
 Chemical Name: Petroleum Lubricant CAS#: Mixture
 Common Name: PA100, PA200, PA300, PA500, PA550

SECTION 2

COMPOSITION/INFORMATION ON INGREDIENTS

COMMON NAME	CHEMICAL NAME	CAS NO.	%
Hydrotreated Heavy Paraffinic Distillate		64741-18-84	<70
Solvent Neutral Petroleum Base Stock		64742-01-02	<30

Contains no other ingredients now known to be hazardous as defined by OSHA 29 CFR 1910.1000(z).

SECTION 3

FIRE HAZARD DATA

Flash Point: >200°C (COC) >392°F. Slightly combustible.

Thermal Decomposition: Carbon Monoxide and Asphyxiants. May release flammable vapors when heated above flash point.

Extinguishing Media: Carbon Dioxide, dry chemical or foam. Avoid using water, except for cooling container. Water may cause splattering or transport flame.

Threshold Limits: The PEL (OSHA) and the TLV (ACGIH) is 5mg/m³ as an oil mist.

Special Fire Procedures: Recommend SCBA and Personal Protective Equipment be used.

SECTION 4

HEALTH HAZARD AND FIRST AID DATA

Route of Exposure:	Hazard:	First Aid:
EYES	May cause eye irritation. No significant adverse effects expected.	Flush with water at least 15 minutes. Get medical attention if irritation develops or persists.
SKIN	Repeated or prolonged contact may cause irritation which may lead to various skin disorders. Avoid prolonged skin contact.	Wash immediately with soap and water. Remove soiled clothing – launder before reuse. Get medical attention if irritation develops or persists.
INHALATION	No significant adverse health effects are expected to occur on short term exposure.	Remove exposed person to fresh air. If breathing is labored, administer oxygen and obtain immediate medical attention. Get medical attention if toxic symptoms or irritation are observed.
ORAL	Ingestion may cause nausea, diarrhea and stomach discomfort.	DO NOT INDUCE VOMITING. If conscious, give two glasses of water. Get immediate medical attention.

This material has not been identified as a carcinogen by NTP, IARC or OSHA.

SECTION 5

PHYSICAL AND CHEMICAL PROPERTIES AND REACTIVITY

APPEARANCE:	Amber, liquid	Ph:	N/d
BOILING POINT:	>300°C	SOLUBILITY:	Negligible
EVAPORATION POINT:	Less than Ether	SPECIFIC GRAVITY:	.919
FLAMMABILITY:	Combustible	VAPOR DENSITY:	Heavier than air
FLASH POINT:	>200°C	VAPOR PRESSURE:	<0.01mm Hg @ 20°C
ODOR:	Petroleum Odor	VOC%:	Nil

Stability: Normally stable at ambient temperatures and pressure.
Conditions/Materials to Avoid: Oxidizing agents. Do not heat above flash point.
Polymerization: Will not occur.

SECTION 6

TRANSPORTATION AND HANDLING

DOT Shipping Name: Oil, n.o.s.
DOT Shipping Class: Not regulated
UN/NA NUMBER:
GUIDE NUMBER: 27

See 49 CFR part 171.1 through 178.510

Materials classified as DOT combustible Liquids (Flash Point > 141°F and < 200°F) are not regulated by DOT in containers of 110 gallons, or less for domestic shipments.

PERSONAL PROTECTION HANDLING EQUIPMENT

Gloves: Use of nitrile or neoprene gloves are recommended.
Eye Protection: Safety glasses, goggles or face shield are recommended.
Respiratory: SCBA is recommended for confined space entry. Maintain ventilation sufficient to keep atmosphere below TLV.
Clothing: Long sleeve shirt and apron when potential for skin contact exists. Wear neoprene or nitrile rubber boots when necessary to avoid contaminating shoes.

Special Precautions: Avoid storage near open flame or other source of ignition. Excessive misting may cause slippery floors. Proper footwear required. Wash hands before eating, drinking or smoking. Discard contaminated leather gloves and shoes.

SECTION 7

ACCIDENTAL RELEASE PROCEDURES

Corrective Measures: Evacuate all non-essential personnel. Personal protection equipment must be worn, see above section 6. Remove sources of ignition. Prevent entry into sewers and waterways. Contain release, pickup and store in appropriate container for recycling or disposal. Mop up or absorb with diatomaceous earth or other inert material.

Disposal Procedures: Dispose in accordance with Local, State and Federal regulations.

Environment Protection: This material is expected to have adverse effects on marine and plant life. Spills may contaminate drinking water. Prevent contamination of soil, waterways and sewer systems.

SECTION 8

OTHER INFORMATION

TSCA All components of this material are on the US TSCA inventory.
CERCLA Listed

	<u>Health</u>	<u>Fire</u>	<u>Reactivity</u>	<u>PPE</u>
HMIS CODE:	1	1	0	C
NFPA CODE:	1	1	0	

This information is accurate and current to the best of Power Punch Distributors knowledge. Revised 08/19/11