

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: CEMENT MORTARS & GROUTS
PRODUCT CODE:

HMIS CODES: H F R P
1 0 0 E

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Custom Building Products, Inc.
ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201
EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846
DATE REVISED : 2-23-00 NAME OF PREPARER : STEVE TAYLOR
REASON FOR REVISION: AREA CODE TO EMERGENCY/INFORMATION PHONE NO. WAS CHANGED

THE FOLLOWING LIST OF PRODUCTS IS APPLICABLE TO THE MSDS ATTACHED:

STUCCO PATCH
CONCRETE PATCH
✓CUSTOM PLUG
CONCRETE REPAIR MORTAR
GLASS BLOCK MORTAR MIX
CUSTOM FLOAT BEDDING MORTAR
CUSTOM BLEND THINSET (GRAY & WHITE)
MASTER BLEND THINSET (GRAY & WHITE)
NON-SAG THINSET MORTAR
(GRAY & WHITE)SUREBOND THINSET MORTAR
(GRAY & WHITE)PREMIUM BLEND THINSET (GRAY & WHITE)
✓PREMIUM PLUS THINSET (GRAY & WHITE)
CRETE MIX MORTAR (GRAY)
SALTILLO GROUT
WHITE DRY TILE GROUT
TROWEL N'SEAL ANTIFRACTURE MEMBRANE (POWDER PT.)

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

COMPONENTS %	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE mm Hg @ TEMP	Wt.
		OSHA PEL	ACGIH TLV		
SILICA, CRYSTALLINE	14808-60-7	.1mg/m3	.1mg/M3	N/A	
PORTLAND CEMENT	65997-15-1	5mg/m3	10mg/m3	N/A	
LIMESTONE	1317-65-3	5mg/m3	10mg/m3	N/A	

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: N/A
VAPOR DENSITY: N/A
SOLUBILITY IN WATER: SLIGHT
APPEARANCE AND ODOR: COLORED POWDER NO ODOR

SPECIFIC GRAVITY (H2O=1): 2.4
EVAPORATION RATE: N/A

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: NONE KNOWN
NON FLAMMABLE.

SPECIAL FIREFIGHTING PROCEDURES
NONE REQUIRED

UNUSUAL FIRE AND EXPLOSION HAZARDS
NONE REQUIRED

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID
NONE

INCOMPATIBILITY (MATERIALS TO AVOID)
STRONG ACIDS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
REACTION WITH STRONG ACIDS WILL RELEASE CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
CHRONIC: CEMENT DUST CAN CAUSE INFLAMMATION OF THE LINING TISSUE OF THE
INTERIOR OF THE NOSE AND INFLAMMATION OF THE EYE. HYPERSENSITIVE INDIVIDUALS
MAY DEVELOP AN ALLERGIC DERMATITIS (skin rash).

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
ACUTE: WET CEMENT, ESPECIALLY AS AN INGREDIENT IN PLASTIC (unhardened)
CONCRETE, CAN DRY THE SKIN AND CAUSE ALKALI BURNS. CEMENT DUST CAN IRRITATE
THE EYES.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
NONE

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
NONE

HEALTH HAZARDS (ACUTE AND CHRONIC)
THIS PRODUCT CONTAINS ONE OR MORE CHEMICALS KNOWN TO THE STATE OF CALIFORNIA
TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. THE STATE OF
CALIFORNIA (PROP. 65) REQUIRES THE ABOVE WARNING IN THE ABSENCE OF DEFINITIVE
TESTING TO PROVE THAT THE DEFINED RISKS DO NOT EXIST. WE BELIEVE THIS PRODUCT
COMPLIES WITH ALL OTHER APPLICABLE STATE AND FEDERAL LAWS AND REGULATIONS
GOVERNING MANUFACTURE, DISTRIBUTION AND INTENDED USE.

CARCINOGENICITY: NTP? YES IARC MONOGRAPHS? YES OSHA REGULATED? YES
THERE IS SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY OF CRYSTALLINE SILICA
TO EXPERIMENTAL ANIMALS AND HUMANS.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
HYPERSENSITIVE INDIVIDUALS MAY DEVELOP SKIN RASH.

EMERGENCY AND FIRST AID PROCEDURES
EYE CONTACT: IRRIGATE EYES WITH WATER; CONSULT PHYSICIAN IMMEDIATELY.
SKIN CONTACT: WASH EXPOSED AREAS WITH SOAP AND WATER IMMEDIATELY.
INHALED: WEAR APPROVED RESPIRATOR IN DUSTY ENVIRONMENT.
INGESTION: INDUCE VOMITING IF VICTIM IS CONSCIOUS. CONSULT PHYSICIAN.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
CLEAN-UP USING DRY METHODS THAT DO NOT DISPERSE DUST INTO THE AIR.
AVOID BREATHING THE DUST. EMERGENCY PROCEDURES ARE NOT REQUIRED.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
KEEP IN DRY LOCATIONS.

OTHER PRECAUTIONS

NONE

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

APPROVED NIOSH RESPIRATOR.

VENTILATION

USE MECHANICAL VENTILATION TO KEEP DUST EXPOSURE BELOW THE TLV RANGES.

PROTECTIVE GLOVES

IMPERVIOUS GLOVES SHOULD BE WORN TO, PREVENT SKIN CONTACT.

EYE PROTECTION

SAFETY GLASSSES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

THE USE OF BARRIER CREAMS OR GLOVES IMPERVIOUS BOOTS AND CLOTHING TO PROTECT
THE SKIN FROM CONTACT WITH WET CEMENT.

WORK/HYGIENIC PRACTICES

GOOD HOUSEKEEPING PROCEDURES SHOULD BE FOLLOWED AT ALL TIMES.

===== SECTION IX - DISCLAIMER =====

DISCLAIMER

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT
WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE
ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT,
APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.